

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number
WO 2005/059252 A1

(51) International Patent Classification⁷: **E01B 5/08**

(21) International Application Number:
PCT/SE2004/001850

(22) International Filing Date:
13 December 2004 (13.12.2004)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0303395-8 16 December 2003 (16.12.2003) SE

(71) Applicant and

(72) Inventor: SUNDGREN, Anders [SE/SE]; Nyåkersvägen
40, S-650 17 Sunderbyn (SE).

(74) Agents: GRANSTRÖM, Lars-Eric et al.; Zacco Sweden
AB, P.O. Box 23101, S-104 35 Stockholm (SE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: GUIDE RAIL OF COMPOUND TYPE AND A METHOD FOR MANUFACTURING SUCH A RAIL



(57) Abstract: The invention concerns a guide rail of compound type and a method of manufacturing such a guide rail. The guide rail is made like a railway rail or similar and intended for guiding interaction with a wheel of a unit travelling along the rail, comprising a long outer rail (4) made of sheet metal exhibiting the shape of a longitudinal open channel with defined inside (9) and outside (10), a long base rail (5) exhibiting a foot (1) for mounting the rail to a surface, a web (2) extending from the foot supporting a main part (3), which, in comparison to the web, is thicker and serves as a receptacle (11) for receiving and supporting the outer rail, whereby the outer rail has an outer profile that has been chosen to provide a guiding interaction with the wheel. According to the invention, the inside (9) of the outer rail (4) and the receptacle section (11) exhibit opposing section shapes, that the outer rail (4) has a yield limit exceeding that of the base rail (5) and that both parts are joined together by adhesive binding such as welding or gluing.